4602.**

2.8 (.110) TYPE SERIES · RECEPTACLES

For male (mm) 2,8x0,8

Wire size mm² (AWG) 0,2-0,6 (24-20)

Ø Insulation (mm) 1,5-2 FLR

Materials, temperature and contact resistance

Part nr.	Material	Finishing	Max. Temp. (ºC)	Contact Resist (mΩ)
4602.00	Brass	Natural	110	1.75
4602.01	Brass	Pre-tin-plated	120	1.50

Material thickness (mm) 0,25

Max. rated current

Wire section	4602.00 / 01
0.20 mm²	2A
0.25 mm²	2A
0.35 mm²	3A
0.50 mm²	5A
0.60 mm²	5.5A

Compatible connectors 22814**

Insertion / Withdrawal forces

	4602.00 / 01
1st Insertion (max)	15N[1]
6th Withdrawal (min)	9N[1]

[1] Valid for Natural brass tab

Application tool MN4600

Wire strip length 4.0 (±0.3) mm

Crimping parameters & pull out force

Wire section (±10%)	Conductor		Insulator	Pull-out force (N)
	Height (mm)	Width (mm)	Width (mm)	
0.20 mm²	0.90 (±0.03)	1.55 (±0.03)	2.30 (±0.10)	28N @ 60s
0.30 mm²	0.95 (±0.03)	1.55 (±0.03)	2.30 (±0.10)	28N @ 60s
0.50 mm²	1.05 (±0.03)	1.56 (±0.03)	2.31 (±0.10)	56N @ 60s
0.60 mm²	1.10 (±0.05)	1.56 (±0.05)	2.30 (±0.10)	56N @ 60s

Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Winding number 15000


Approvals

RoHS

4602.**

2.8 (.110) TYPE SERIES · RECEPTACLES

Drawing






4602.00 NATURAL BRASS
2.8 (.110) TYPE SERIES · RECEPTACLES


Derating curve

Current carrying capacity vs. Ambient temperature



Temperature rise curve

Terminal temperature rise due to the current carried




Valid for Natural brass tab

4602.01 PRE-TIN-PLATED BRASS
2.8 (.110) TYPE SERIES · RECEPTACLES


Derating curve

Current carrying capacity vs. Ambient temperature



Temperature rise curve

Terminal temperature rise due to the current carried



Valid for Natural brass tab

4602.**

2.8 (.110) TYPE SERIES · RECEPTACLES

Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A1	Datasheet generated automatically [A1]	2026-11-18	O.Roura (Engineering Dept.)	E.Roura (Laboratory Dept.)

Escubedo Connection Systems, S.A.U. · 17843 Riudellots de la Creu · Girona · Spain
Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com