

4943J**

6.3 (.250) TYPE SERIES · RECEPTACLES

SELF-LOCKING RECEPTACLES. LOW INSERTION TERMINALS.



Specification Self-locking terminals under TP design

Typology Extra low insertion

For male (mm) 6,3x0,8

Wire size mm² (AWG) 0,2-0,6 (24-20)

Ø Insulation (mm) 1,1-2,1

Materials, temperature and contact resistance

Part nr.	Material	Finishing	Max. Temp. (°C)
4943J00	Brass	Natural	110
4943J01	Brass	Pre-tin-plated	120
4943J02	Brass	Tin plated	120
4943J24	Steel	Nickel-plated	300

Material thickness (mm) 0,4

Insertion / Withdrawal forces

	4943J00 / 01 / 02 / 24
1st Insertion (max)	20N ¹
1st Withdrawal (max)	25N ¹
1st Withdrawal (min, locking enabled)	90N ¹

¹ Valid for Natural Brass Tab

Security function Self-locking function prevents disconnection by pulling the cable.
 Disconnection is possible disabling the locking function, pressing the lever manually or sliding the connector (see withdrawal forces).
 It allows several connections-disconnections maintaining the functional features.

Application tool MN4943

Wire strip length 5.5 (±0.5) mm

Crimping parameters & pull out force

Wire section (±10%)	Conductor		Insulator	Pull-out force (N)
	Height (mm)	Width (mm)	Width (mm)	
0.20 mm ²	1.10 (±0.03)	1.95 (±0.03)	3.16 (±0.10)	28N @ 60s
0.25 mm ²	1.15 (±0.03)	1.95 (±0.03)	3.15 (±0.10)	28N @ 60s
0.35 mm ²	1.20 (±0.03)	1.95 (±0.03)	3.15 (±0.10)	40N @ 60s
0.50 mm ²	1.25 (±0.03)	1.96 (±0.03)	3.14 (±0.10)	56N @ 60s
20 AWG	1.25 (±0.03)	1.95 (±0.03)	3.15 (±0.10)	58N @ 60s
22 AWG	1.20 (±0.03)	1.95 (±0.03)	3.15 (±0.10)	36N @ 60s
24 AWG	1.10 (±0.03)	1.95 (±0.03)	3.15 (±0.10)	22,3N @ 60s

Values only valid for the application tool specified upwards. The insulator widths are only indicative as they are dependent on the sheath thickness of the wire used.

Winding number 8000

Compatible connectors 26418**, RS5412**-K, RS5413**-K, RS5414**-K, RS5415**-K

4943J**

6.3 (.250) TYPE SERIES · RECEPTACLES

SELF-LOCKING RECEPTACLES. LOW INSERTION TERMINALS.



Max. rated current

Wire section	4943J00 / 01 / 02 / 24
0.20 mm ²	2A
0.25 mm ²	2A
0.35 mm ²	6A
0.50 mm ²	8A
0.60 mm ²	8A


Approved regulations

Part nr.	Approval	Standard	File	Certified framework
4943J00	UL	UL 310	E211727	AWG 24-20 (MV-10 Stranded Cu) / MN4943
4943J01	UL	UL 310	E211727	AWG 24-20 (MV-10 Stranded Cu) / MN4943
4943J02	UL	UL 310	E211727	AWG 24-20 (MV-10 Stranded Cu) / MN4943
4943J24	UL	UL 310	E211727	AWG 24-20 (MV-10 Stranded Cu) / MN4943

Approvals



Drawing




4943J00 NATURAL BRASS

6.3 (.250) TYPE SERIES · RECEPTACLES
SELF-LOCKING RECEPTACLES. LOW INSERTION TERMINALS.




Derating curve

Current carrying capacity vs. Ambient temperature



Temperature rise curve

Terminal temperature rise due to the current carried



Valid for Natural Brass Tab

4943J02 TIN PLATED BRASS


6.3 (.250) TYPE SERIES · RECEPTACLES

SELF-LOCKING RECEPTACLES. LOW INSERTION TERMINALS.




Derating curve

Current carrying capacity vs. Ambient temperature



Temperature rise curve

Terminal temperature rise due to the current carried



Valid for Natural Brass Tab


4943J24 NICKEL-PLATED STEEL

6.3 (.250) TYPE SERIES · RECEPTACLES SELF-LOCKING RECEPTACLES. LOW INSERTION TERMINALS.




Derating curve

Current carrying capacity vs. Ambient temperature



Temperature rise curve

Terminal temperature rise due to the current carried



Valid for Natural Brass Tab

4943J****6.3 (.250) TYPE SERIES · RECEPTACLES****SELF-LOCKING RECEPTACLES. LOW INSERTION TERMINALS.****Disclaimer**

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A4	Update datasheet	2025-10-01	D. Yabar (Engineering Dept.)	E. Roura (Laboratory Dept.)
A3	Update 1st Withdrawal value to 25N	2025-06-13	D. Yabar (Engineering Dept.)	E. Turon (Engineering Dept.)
A2	Update 'Approved regulations'	2025-04-29	E. Roura (laboratory dept.)	E. Turon (engineering dept.)
A1	Datasheet generated automatically [A1]	2025-02-25	D. Yabar (Engineering Dept.)	Engineering Dept.