PRODUCT DATASHEET

9322.**

6.3 (.250) TYPE SERIES · RECEPTACLES FOR CONNECTOR

Description

The terminal consists of two components: a conductive connection and a spring manufactured from AISI 301 stainless steel.

For male (mm)

6,3x0,8

Wire size mm² (AWG)

0,5-1 (20-18)

Ø Insulation (mm)

1,4-2,1

Materials, temperature and contact resistance

Part nr.	Material	Finishing	Max. Temp. (ºC)
9322.31	Bronze	Pre-tin-plated	130
9322.83	Cu. Alloy	Silver-plated	150

Material thickness (mm)

0,4

Max. rated current

Wire section	9322.31 / 83
0.50 mm²	8A
0.75 mm²	10A
1.00 mm²	12A

Wire strip length

3.8 (±0.5) mm

Winding number

2400

Approvals

RoHS

Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A1	Datasheet generated automatically [A1]	2026-11-18	O.Roura (Engineering Dept.)	E.Roura (Laboratory Dept.)

Escubedo Connection Systems, S.A.U. · 17843 Riudellots de la Creu · Girona · Spain
Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com