

R5534**-K

RAST 5 TERMINALS AND CONNECTORS · FLAGS FOR CONNECTOR



Specification Flag Holder RAST 5 Crimp Connect Connectors

Ways 4

Thermal Characteristics

Part nr.	Raw material	Color	Flammability Class (UL 94)	Glow Wire Test (GWT) (IEC60695-2-11)	Glow Wire Flammability Index (IEC60695-2-12)	RTI electrical (Max. Operating Temp.)
R553410-K	PA66V2	Natural	V2	(T.B.D.)	850°C	105°C
R553430-K	PA66V0	Natural	V0	(T.B.D.)	960°C	140°C
R553440-K	NO FLAME	Natural	V2	(T.B.D.)	960°C	130°C
R553460-K	PAV0NF	Natural	V0	(T.B.D.)	960°C	130°C

For other materials and colors ask to: info@escubedo.com

Counterparts R5694**-K

Compatible terminals 5332.**, 5332F**, 5333.**, 5333F**, 5334.**, 5335.**, 5336.**

Insertion / Withdrawal forces

	R553410-K / 30 / 40
1st Insertion (max)	12N
1st Withdrawal (min, primary lock only)	50N
1st Withdrawal (min, primary + secondary lock)	50N

Approved regulations

Part nr.	Approval	Standard	File	Certified framework
R553410-K ¹	UL	UL 1977	E245592	V2 / RTI Elec., Max. Operating Temp, 65°C
R553430-K ¹	UL	UL 1977	E245592	V0 / RTI Elec., Max. Operating Temp, 110°C
R553440-K ¹	UL	UL 1977	E245592	V2 / RTI Elec., Max. Operating Temp, 105°C
R553440-K ²	VDE	EN 61984	DE1-70504/B1	

¹ Cat. No. meets with the standard UL1977 as a component of UP-RAST5 full connection system

5332.**; 5333.** - 12A/600V (USR, CND)


5334.**; 5335.** - 15A/600V (USR, CND)

² Cat. No. meets with the standard EN611984 as a component of UP-RAST5 connection Series. 400V; max 20A

Approvals



Drawing



Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A1	Datasheet generated automatically [A1]	2026-10-09	O.Roura (Engineering Dept.)	E.Roura (Laboratory Dept.)

Escubedo Connection Systems, S.A.U. · 17843 Riudellots de la Creu · Girona · Spain
 Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com