ESCUBEDO CONNECTION SYSTEMS

PRODUCT DATASHEET

RT5433**-K

6.3 (.250) TYPE SERIES · CONNECTORS

Specification RAST 5 Crimp Connect Connectors

Ways 3

Thermal Characteristics


Part nr.	Raw material	Color	Flammability Class (UL 94)	Glow Wire Test (GWT) (IEC60695-2-11)	Glow Wire Flammability Index (IEC60695-2-12)	RTI electrical (Max. Operating Temp.)
RT543390-K	PA66 V0	Natural	V0	750ºC	960ºC	130ºC

For other materials and colors ask to: info@escubedo.com

Counterparts RT5433**TPA

Compatible terminals 9322.**, 9320.**, 9324.**, 9326.**

Drawing



Disclaimer

Data obtained from Escubedo Laboratory essays, using own methodology, cablings, equipment and original crimping tools, done in laboratory conditions and following the indicated standards, errors and omissions excepted. This document has no contractual meaning and it is publicised only for informative purposes. It can be changed without prior notice. The end customer has the sole responsibility to check these characteristics in its environment and with its own components, manufacturing methods and equipment. See also the full range product overview if available. For further information please visit our web site or contact us

Rev. Nr.	Concept	Date	Created/Revised	Approved
A1	Datasheet generated automatically [A1]	2026-11-19	O.Roura (Engineering Dept.)	E.Roura (Laboratory Dept.)

Escubedo Connection Systems, S.A.U. · 17843 Riudellots de la Creu · Girona · Spain
Tel.: 34 972 171 706 · Fax: +34 972 171 714 · info@escubedo.com · www.escubedo.com